



BAT30 | BAT45

Stacked

Tumble Dryer

FEATURES

- Standard galvanized drum
- Stainless steel front panel
- Large door opening for easy loading & unloading
- Self cleaning lint screen

OPTIONS

- Coin operated
- Stainless steel drum
- Reversing drum

CONTROLS OPTIONS

- Evolis / Evolis Elite – fully programmable and customizable cycles 5" touch screen.
- User-friendly screen with operating instructions built in as part of the control
- Complete control content available in 34 languages

C.A.R.E (Combustion Auto Response Equipped)
-A response to laundry combustion
-helps suppress early laundry fire by constantly monitoring the temperature in the drum
-in case of excessive temperature, linen is sprayed with water

C.A.R.E.™ for Vend

C.A.R.E.™ for Vend Fire Suppression for BAT30 BAT45 (Stacked Tumble Dryer) delivers automatic, sensor activated protection for self service laundromats. In the unlikely event of a linen fire inside the drum, the optional multiport water manifold saturates the load. It integrates with the dryer's controls, requires no user action, helping reduce downtime, damage and overall risk in your laundromat.



Safety:

Helps prevent fire spread to other machines and the Laundromat



Temperature Monitoring:

Always-on sensors for 24/7 protection



Double Pocket Protection:

Reduces heat damage to equipment and interiors



Automatic Detection:

Instant, hands-free response with no user action required



FIRE SUPPRESSION SYSTEM

For maximal safety of your operations



LOW ENERGY CONSUMPTION

Lower energy and utility costs, lower linen replacement costs



CLOUD-BASED PLATFORM

to easily monitor your laundry everywhere and at any time



			BAT30	BAT45
CAPACITY				
Capacity 1:18	kg (lb)		2 x 17(38)	2 x 24(53)
Capacity 1:22	kg (lb)		2 x 14(31)	2 x 20(41)
Drum volume	l		2 x 300	2 x 420
Drum diameter	mm		Ø 762	Ø 838
AIRFLOW	l/sec		310 - 380	570
MOTORS				
Fan	kW		0,40	0,40
Drive	kW		0,40	0,40
NOISE LEVEL	dBA		63	65
GAS HEATING				
Gas connection	NPT		1/2"	1/2"
			A Market 1/2" BSPT	A Market 1/2" BSPT
Energy per pocket	kW		16.1 - 21.4	23.4 - 27.8
	kBTU/h		55 - 73	80 - 95
ELECTRICAL HEATING				
Electrical Specs	Gas			
	B		100-120V/50-60Hz/1Ph	-
	X		200-240V/50-60Hz/1-3Ph	-
	P		380-415V/50-60Hz/3Ph	-
	N		440-480V/50-60Hz/3P	-
	Electric			
	G		230-240V/50-60Hz/3Ph	-
	H		380V/50-60Hz/3Ph	-
	J		400-415V/50-60Hz/3Ph	-
	L		460-480V/50-60Hz/3Ph	-
Energy per pocket	kW		12 - 21	-
EXHAUST	mm		150 - 200	250
DIMENSIONS				
H*W*D	mm		800x1110x1940	875x1260x20650
Net weight	kg		265 - 275	315
TRANSPORT DATA				
Packed H*W*D	mm		830x1190x2030	900x1370x2160
Gross weight	kg		280 - 290	335

	A	B	C	D	E	F	G	H	I	J	K	L*	M*	N*	O*	P*
BAT30	710	1245	1225	290	270	635	730	1100	695	800	1940	620	465	40	1575	1133
BAT45	810	1280	1250	260	235	735	830	1260	770	875	2065	635	490	40	1650	1311
											D	W	H			

*Fire suppression system optional - may not be on machine.

