

FCI800

Cylinder Heated Ironer



FEATURES

- Finger protection and emergency button for more safety
- Automatic cool down
- Indication of ironing speed and temperature
- Frequency controlled motor
- Overdimensioned fan for flexible installation
- Reverse mode possible

- Space saving installation against the wall is possible: front return

OPTIONS

- Stop pedal
- Vacuum table

CONTROLS OPTIONS

- MCX- Easy to operate microprocessor



LARGE SURFACE CONTACT WITH LINEN
over an angle of 300° for high ironing capacity



AUTO ADJUSTABLE IRONING SPEED TECHNOLOGY
according to the residual moisture



OVERHEATING CHECK SYSTEM
For increased safety of your operations



FCI3186/800

ROLLER DIAMETER	mm	800
USEFUL ROLLER LENGTH	mm	3186
HEATING		
Electric	kW	75
Gas	kW	110*
Steam	Kg	190
MOTORS		
Roller	kW	0,9
Fan	kW	2x0,55/0,75
IRONING CAPACITY**		
Electric	kg/h	195
Gas	kg/h	195
Steam	kg/h	195
ROLLER SPEED	m/min	3-15
ELECTRIC CONNECTION		380-415V 3AC+N 50/60 Hz, 208-240V 3AC 50/60 Hz, 380-415V 3AC-N 50/60 Hz, 440-480V 3AC 60 Hz
DIMENSIONS		
H*W*D	mm	1985×4260×1915
Net weight (EL/G/S)	kg	2610 / 2480 / 2900
TRANSPORT DATA		
HxWxD	mm	2080×4380×2080
Packed weight (EL/G/S)	kg	2870 / 2740 / 3160

* G20, 20 mbar ** According to ISO 9398-1

