

BS30 | BS50



STAX

Washer-Extractor / Tumble dryer Stax-X

FEATURES


- **Redesigned produce** to maximize ROI per square foot for laundries where space is limited with interior design look premium and unique design in laundromat store.
- **New design soap dispenser** Enhanced self-cleaning reduces downtime and labor costs.
- **Fewer front fasteners** gives quick access to key washer-extractor components that improve service ability.
- **Easy and convenience** with no need to use a laundry cart to transfer loads across the store to the tumble dryer section.
- **200 G-force Extraction Speed** Fast spinning that removes more water make your clothes dry quicker.

CONTROLS OPTIONS


- **Built-in control design** for user-friendly with operating and control.
- **11 cycles - Washer-Extractor** (9 basic cycles options and 2 custom cycles)
- **5 basic cycles - Tumble dryer** (high, medium, low, delicate, no heat)
- **Speed Cycle option** for those who want to get in and out quickly.
- **Flexible price setting & additional revenue opportunities** with customizable cycle modifiers, time-of-day pricing and lucky cycle options.
- **On-screen timer indicator** customers know exactly how much time cycle will take.
- **Flexible Payment Options** - Single Drop, Dual Drop, Token, E-Drop and Prep for Coin



Aries Micro Control



Washer



Dryer

		BS30		BS50	
		Washer-Extractor	Tumble Dryer	Washer-Extractor	Tumble Dryer
Control Option	kg (lb)	Aries Micro		Aries Micro	
Capacity Overall	mm (in)	30 (14) x 2		50 (23) x 2	
Overall Width	mm (in)	31.4 (797)		34.4 (875)	
Overall Depth	mm (in)	46.6 (1175)		52.2 (1325)	
Overall Height	mm (in)	79.7 (2023)		84.3 (2141)	
Cylinder Diameter	mm (in)	24.0 (610)	30.0 (762)	26.3 (668)	33.0 (838)
Cylinder Depth	mm (in)	16.0 (406)	26.0 (660)	20.3 (515)	30.0 (762)
Cylinder Volume	cu. ft (liters)	4.2 (119)	10.6 (300)	6.3 (178)	14.8 (419)
Reversing Cylinder	mm (in)	-	Standard	-	Standard
Door Opening Size	mm (in)	19.3 (489)	28.4 (720)	23.0 (585)	32.0 (812)
Door Bottom to Floor	mm (in)	14.0 (356)	51.3 (1303)	14.5 (368)	52.3 (1328)
Water Inlet	mm (in)	2 x 0.75 (19)	-	2 x 0.75 (19)	-
Drain Diameter	mm (in)	1 x 3 (76)	-	1 x 3 (76)	-
Drain Height to Floor	mm (in)	4.3 (108)	-	4.5 (115)	-
Heat Input Power	Btu/hr (kW, Mj/hr.)	-	73,000 (21.4, 77.0)	-	95,000 (27.8, 100)
Gas Connection	in	-	1/2 NPT	-	1/2 NPT
Air Outlet	mm (in)	-	8.0 (200) Elliptical	-	10.0 (250) Elliptical
Airflow	cfm (l/sec)	-	400 (190)	-	600 (285)
Motor	kw	-	0.5 (0.37)	-	0.5 (0.37)
	Fan Drive	-	0.5 (0.37)	-	0.5 (0.37)
Total # of Speeds		1 (0.75)	0.5 (0.37)	2 (1.5)	0.5 (0.37)
		9	-	9	-
Cylinder Speeds	Gentle	34 (0.4)	-	33 (0.4)	-
- RPM (G-Force)	Wash	48 (0.8)	-	46 (0.8)	-
	Distribution	86 (2.5)	-	82 (2.5)	-
	Very Low	282 (27)	-	269 (27)	-
	Low	485 (80)	-	464 (80)	-
	Medium	542 (100)	-	518 (100)	-
	High	606 (125)	-	579 (125)	-
	Very High	664 (150)	-	635 (150)	-
	Ultra High	766 (200)	-	733 (200)	-
Electrical Specs - amps	Gas X	200-240V/50-60Hz/1-3Ph	7 (1 Ph)	5 (1 Ph)	8 (1 Ph)
	Electric H	380V/50-60/3Ph	4 (3 ph)	3 (3 Ph)	5 (3 Ph)
			3	33	-
Shipping Dimensions Approx.	Width	36.5 (927)		36.5 (927)	
	mm (in)	48.0 (1219)		54.0 (1372)	
	Depth	84.0 (2134)		89.0 (2261)	
Net Weight	Height				
	lb(kg)	770 (350)		920 (423)	
Shipping Weight	lb(kg)	800 (365)		955 (435)	