

BSG30 | BSG50



STACKED

Washer-Extractor / Tumble dryer

FEATURES

- Ideal for limited space settings
- Increases wash capacity
- Improves throughput
- Minimal front fasteners give quick access to key washer-extractor components to improve serviceability
- Supports a higher volume than typical retail and light commercial products are able to support
- More than double production with higher capacity and faster wash times
- Reliability and durability that drastically outperforms retail or light commercial options
- IPSO stacked washer-extractor/tumble dryer is a unique product that truly delivers increased productivity.
- Featuring the Evolis Touch Control.

CONTROLS OPTIONS

- Available with EVOLIS touch control for Vend.
- 7", full color touch screen display with swipe function: very intuitive for users
- User-friendly screen with operating instructions built in as part of the control
- Complete control content available in 34 languages
- Wireless communication enabling programming & firmware updates through cloud
- Automated service reminders remind users to maintenance tasks
- Warranty IPSO Connect: interactive dashboard offers operational performance info on mobile device
- 5 standard dry programmes (High, Medium, Low, Delicate, No Heat)
- 15 easy-to-use washer cycle modifier



FIRE SUPPRESSION SYSTEM

For maximal safety of your operations



LOW ENERGY CONSUMPTION

Lower energy and utility costs, lower linen replacement costs



CLOUD-BASED PLATFORM

To easily monitor your laundry everywhere and at any time



EXTRA LARGE DOOR OPENING

For easy loading and unloading



HIGH CAPACITY WATER INLETS

For shorter wash cycles

			BSG30		BSG50	
			Washer-Extractor	Tumble Dryer	Washer-Extractor	Tumble Dryer
Control Option	kg (lb)		EVOLIS Touch		EVOLIS Touch	
Capacity Overall	mm (in)		30 (14)		50 (23)	
Width	mm (in)		31.4 (797)		34.4 (875)	
Overall Depth	mm (in)		45.5 (1152)		51.3 (1302)	
Overall Height	mm (in)		79.7 (2023)		84.3 (2141)	
Cylinder Diameter	mm (in)		24.0 (610)	30.0 (762)	26.3 (668)	33.0 (838)
Cylinder Depth	m m (in)		16.0 (406)	26.0 (660)	20.3 (515)	30.0 (762)
Cylinder Volume	cu. ft (liters)		4.2 (119)	10.6 (300)	6.3 (178)	14.8 (419)
Reversing Cylinder	mm (in)		-	Standard	-	Standard
Door Opening Size	mm (in)		14.3 (363)	22.6 (574)	16.3 (414)	26.9 (683)
Door Bottom to Floor	mm (in)		14.0 (356)	51.3 (1303)	14.6 (370)	52.3 (1328)
Water Inlet	mm (in)		2 x 0.75 (19)	-	2 x 0.75 (19)	-
Connection Drain	mm (in)		1 x 3 (76)	-	1 x 3 (76)	-
Diameter	m m (in)		4.3 (108)	-	4.5 (115)	-
Drain Height to Floor	Btu/hr (kW, Mj/hr.)		-	73,000 (21.4, 77.0)	-	95,000 (27.8, 100)
Heat Input Power	in		-	1/2 NPT	-	1/2 NPT
Gas Connection	m m (in)		-	8.0 (200) Elliptical	-	10.0 (250) Elliptical
Air Outlet	cfm (l/sec)		-	400 (190)	-	600 (285)
Airflow	kw	Fan	-	0.5 (0.4)	-	0.5 (0.4)
Motor		Drive	1 (0.75)	0.3 (0.2)	2 (1.5)	0.3 (0.2)
			9	-	9	-
Total # of Speeds	Gentle		34 (0.4)	-	33 (0.4)	-
Cylinder Speeds	Wash		48 (0.8)	-	46 (0.8)	-
- RPM (G-Force)	Distribution		86 (2.5)	-	82 (2.5)	-
	Very Low		282 (27)	-	269 (27)	-
	Low		485 (80)	-	464 (80)	-
	Medium		542 (100)	-	518 (100)	-
	High		606 (125)	-	579 (125)	-
	Very High		664 (150)	-	635 (150)	-
	Ultra High		766 (200)	-	733 (200)	-
Electrical	Gas					
Specs - amps	x	200-240V/50/60/1/3	15	10	15	10
Shipping		Width	34.5 (876)		35.5 (902)	
Dimensions	m m (in)	Depth	47.0 (1194)		54.0 (1372)	
Approx.		Height	83.0 (2108)		89.0 (2261)	
Net Weight	lb(kg)		770 (349)		910 (413)	
Shipping Weight	lb(kg)		787 (357)		930 (422)	
Agency Approvals			CSA/UL/KGS/KTL/TISI/Global-Mark		CSA/UL/KGS/KTL/TISI/Global-Mark	